


GX Series

40 Volts • Torque range : 0,28 to 4,4 Nm • Auto-shut off • CE • 




Main Benefits

- Higher productivity : thanks to high Brushless motor efficiency!
- Higher comfort : thanks to improved ergonomy and reduced sound level and heat!
- Increased economy : thanks to brushless motor (triple the life time of the motor).
- Reduced maintenance : The best Mean Time Between Failure (MTBF) ever reached until now (no carbon brush, trigger and reverse contactless switches, over-heat and over-current built in alarms protecting the screwdrivers).
- Increased production quality : thanks to ESD protection, accurate clutch +/- 3 % and Softstop clutch Mechanism.

STANDARD Series : GX

Model	Torque Range (Nm)	Rotation speed (rpm)	Starting system	Weight (Kg)	Noise level (dBA)	Vibrations level (m/sec ²)	Code
GX-150 ESD	0,3 - 1,47	800 to 1700	Lever	0,52	<70	<2,5	1027422
GX-220 ESD	0,6 - 2,15	600 to 1250	Lever	0,52	<70	<2,5	1027423
GX-450 ESD	1 - 4,41	300 to 650	Lever	0,52	<70	<2,5	1027424
GX-150 P ESD	0,3 - 1,47	800 to 1700	Push to Start	0,52	<70	<2,5	1027425
GX-220 P ESD	0,6 - 2,15	600 to 1250	Push to Start	0,52	<70	<2,5	1027426
GX-450 P ESD	1 - 4,41	300 to 650	Push to Start	0,52	<70	<2,5	1027427

Option : Soft start and double hit functions : Add suffix  in your order . Exemple : GX 80 + ESD

TIMER & AUTOREVERSE Series : GXT

(fasten at preset angle/time, Automatic Reverse/forward sequence – ideal for tapping operation, helicoil fastening, pre-assembly...)

Model	Torque Range (Nm)	Rotation speed (rpm)	Starting system	Weight (Kg)	Noise level (dBA)	Vibrations level (m/sec ²)	Code
GXT-150 ESD	0,3 - 1,47	800 to 1700	Lever	0,52	<70	<2,5	1075304
GXT-220 ESD	0,6 - 2,15	600 to 1250	Lever	0,52	<70	<2,5	1075305
GXT-450 ESD	1 - 4,41	300 to 650	Lever	0,52	<70	<2,5	1075306

AUTOMATION Series : GXA

(Automatic spindle with remote start)

Model	Torque Range (Nm)	Rotation speed (rpm)	Starting system	Weight (Kg)	Noise level (dBA)	Vibrations level (m/sec ²)	Code
GXA-150 ESD	0,3 - 1,47	800 to 1700	Remote	0,6	<70	<2,5	1027434
GXA-220 ESD	0,6 - 2,15	600 to 1250	Remote	0,6	<70	<2,5	1027435
GXA-450 ESD	1 - 4,41	300 to 650	Remote	0,6	<70	<2,5	1027436

