

OHTAKE

Precision Screw Feeder

Automatic Screw Feeder

OM-26

Constant velocity feeding



Radial Indexing Escaper

Radial indexing escaper prepares 3 screws for quickest pick up!



NEW

BIG STORAGE 500cc

Large screw storage capacity

Example: 1300pcs (M3.0 x 12mm)

Old model: NJ:150cc NSB:80cc

SCREW SIZE M2~M6

Applicable Screw size M2.0 ~ M6.0

(Non-iron screws cannot be used)

Applicable Screw Length (exc. Head)

Up to 25mm

Interchangeable rails for handling varying screw diameters M2.0 ~ M6.0

Model Name	OM-26
Size(mm)	119(W) x 226(D) x 152(H)mm
Weight(including rail)	3.08Kg
Power Source	In:AC100~240V Out:DC15V 1A AC adapter
Protection & Recovery Circuit	Motor overload stop, Protection circuit for reverse power connection
Applicable Screw	From M2.0 to M6.0 (to the table for applicable rails)
Applicable Screw Length(under head)	Up to 25mm
Scooping Camber Capacity	500cc

OHTAKE · ROOT · KOGYO CO., LTD
MADE IN JAPAN

<http://www.ohtake-root.co.jp/>

※ The specifications and appearance may be changed without prior notice to improve quality of machine.